



## SPECIFICATIONS

### Mercury® Diesel: 2.8L (Tier 2)



<b>Power mhp / kW</b>	220 / 160
<b>Transmission and Ratio</b>	TM 485A 2.09:1, 2.40:1 ZF 631V 2.0:1, 2.5:1
<b>Bore and stroke</b>	3.70 x 3.94" / 94 x 100 mm
<b>Maximum RPM (WOT)</b>	3800
<b>Engine type</b>	Inline 4
<b>Displacement (L)</b>	2.8
<b>Weight (engine only)</b>	794 lbs / 360 kg
<b>Weight (incl. transmission)</b>	873 lbs / 396 kg
<b>Weight - Bravo One</b>	1025 lbs / 465 kg
<b>Weight - Bravo Two</b>	1041 lbs / 472 kg
<b>Weight - Bravo Three</b>	1052 lbs / 477 kg
<b>Dimensions (L x W x H)</b>	34 x 30 x 31" / 861 x 772 x 793 mm
<b>Cooling system</b>	Closed cooling
<b>Fuel consumption</b>	13.4 gal/hr / 50.6 l/ hr @ 3800 rpm
<b>Compatible drives</b>	Bravo One Bravo Three Bravo Two
<b>Emission</b>	EPA Tier 2
<b>Compatible with SmartCraft digital technology</b>	Yes

© 2016 Mercury Marine. All Rights Reserved.

Reproduction in whole or in part without permission is prohibited. Mercury Marine is a division of Brunswick Corporation.